

EA900

10KVA~120KVA(3/3)

380V

PF 0.9



Features

- High frequency online double-conversion with DSP control
- Modular design, high reliability, easily maintenance
- Double input distribution, higher reliability of system
- Input power factor correction (PFC)
- Wide input voltage range, 50Hz/60Hz frequency self-adaptable
- Support two modes of frequency conversion: 50Hz input/60Hz output and 60Hz input/50Hz output
- Input power factor >0.99, input THDi ≤3%, output THDV ≤3%
- Output power factor 0.9
- High efficiency: load >10%, efficiency ≥90%; load >50%, efficiency ≥93%.
- Digitized charger: flexible charger parameter and battery configuration setting, monitoring battery disconnected on line
- Share battery pack in parallel operation or separate battery pack for different UPS
- Support battery cold start and mains supply self-starting
- 5.7 inches LCD touch screen, friendly human & machine interface
- Perfect protective function in hard and software, robust self diagnose, abundant event log for future check
- Perfect password control technology, including: the first power-on password control, user password control and Maintenance password control.
- Reminders of battery and DC BUS capacitors out of warranty
- Standard emergency power off (EPO)
- Standard RS232/USB/RS485/Dry contact communication port
- Optional SNMP communication port
- Optional N+1 redundancy parallel up to 6 units
- Optional built-in isolation transformer
- Optional battery temperature compensation



Communication port

Rear Panel

1. SNMP(option)
2. RS232
3. RS485
4. USB
5. TEMP COMPENSATION
6. BATTERY PROTECTION
7. DRY CONTACT
8. PARALLEL PORT(option)

Specifications

| MODEL | EA9010 | EA9020 | EA9030 | EA9040 | EA9060 | EA9080 | EA90100 | EA90120 |
|-----------------------------------|----------------|---------------|---------------|---------------|---------------|---------------|----------------|---|
| Capacity | 10KVA 9KW | 20KVA 18KW | 30KVA 27KW | 40KVA 36KW | 60KVA 54KW | 80KVA 72KW | 100KVA 90KW | 120KVA 108KW |
| INPUT | | | | | | | | |
| Rated Voltage | | | | | | | | 380V/400V/415VAC |
| Voltage Range | | | | | | | | 204~520VAC(Load≤50%); 242~520VAC(50%<Load≤70%); 304V~520VAC(70%<Load≤100%) |
| Rated Frequency | | | | | | | | 50/60Hz Auto Sensing |
| Frequency Range | | | | | | | | 40~70Hz |
| Power Factor | | | | | | | | ≥0.99 |
| Total Harmonic Distortion(THDi) | | | | | | | | ≤3% |
| Bypass Voltage Range | | | | | | | | Rated output voltage-40%~ Rated output voltage+20%(Setting available via LCD) |
| OUTPUT | | | | | | | | |
| Voltage | | | | | | | | 380V/400V/415VAC |
| Voltage Regulation | | | | | | | | ± 1% |
| Frequency | | | | | | | | Synchronized with utility on AC mode; (Frequency converter mode:50Hz input and 60Hz output,or 60Hz input and 50Hz output) |
| Waveform | | | | | | | | 50/60Hz on battery mode |
| Crest Factor | | | | | | | | Pure sine wave |
| Total Harmonic Distortion(THDV) | | | | | | | | ≤1%(Linear load);≤3%(Non-linear load) |
| Transfer Time | | | | | | | | Between AC mode and battery mode :0ms Between AC model and bypass mode:0ms |
| Inverter Overload Capability | | | | | | | | 102%~125%:Transfer to bypass after 10mins; 125%~150%:Transfer to bypass after 1mins; >150%: Transfer to bypass after 0.5s |
| Bypass Overload Capability | | | | | | | | ≤150%: Long time running >150%: Shut down after 10s |
| BATTERY | | | | | | | | |
| DC Voltage | | | | | | | | ± 192V(Option: ± 204V/± 216V/± 228V/± 240V) |
| Inbuilt Battery of Standard Model | 32*12V/ 9Ah | 64*12V/9Ah | | | | | | NO |
| Charger Current | | | | | | | | 1~24A(Setting available via LCD) |
| Typical Recharge Time | | | | | | | | 1~24A(Setting available via LCD) 1~48A(Optional) |
| SYSTEM | | | | | | | | |
| Efficiency | | | | | | | | ≥93%,ECO model 98.5% |
| Display Panel | | | | | | | | 5.7 Inches LCD touch screen |
| Alarm | | | | | | | | Battery mode, Battery voltage low, Fans fault etc |
| Maximum Parallel numbers | | | | | | | | 6 |
| EMI | | | | | | | | EN62040~2 |
| EMS | | | | | | | | |
| | | | | | | | | IEC61000~4~2(ESD) |
| | | | | | | | | IEC61000~4~3(RS) |
| | | | | | | | | IEC61000~4~4(EFT) |
| | | | | | | | | IEC61000~4~5(Surge) |
| ENVIRONMENT | | | | | | | | |
| Humidity | | | | | | | | 0~95% RH @ 0~40°C(non-condensing) |
| Noise Level | | | | | | | | ≤60dB |
| MANAGEMENT | | | | | | | | |
| Communication | | | | | | | | RS232,RS485,USB,Dry contact |
| Optional SNMP | | | | | | | | Supports Windows® 98/2000/2003/XP/Vista/2008/Windows® 7/8 |
| PHYSICAL | | | | | | | | |
| Dimension(mm) W*D*H | | | | | | | | 600×800×1360 |
| Packing Dimension(mm) W*D*H | | | | | | | | 720×920×1500 |
| Net/Gross Weight(kg) | 180/200 | 185/205 | 190/210 | 225/245 | 230/250 | 336/376 | 374/414 | Without Inbuilt battery |

● All specifications subject to change without notice.
● Custom-made specifications are acceptable